



Festoon Lighting System Utilising 2-Core Cable & Lighting Adaptors

Designed to work with a range of luminaires, with ES or BC fittings. The festoon comes complete, with additional Lamp Guards, to help protect luminaires from damage or breaks.

Features and Benefits

- **2-Core cables, available in variety of colours, standard or LSOH**
- **Lighting adaptors bespoke with ES or BC fittings**
- **Robust & waterproof design**
- **Cable length and adaptor spacing bespoke to clients specifications**
- **Designed for use with LED bulbs (sold separately)**
- **Quick, safe and easy installation**

Applications

- **Ship Building & Ship Repair**
- **Construction**
- **Tunnelling**
- **Railways**

Specification

Other Parts Specifications:	
Lamp guard material	Nylon
Lamp guard colours available	Yellow
Adaptor Material	Rubber & plastic
Max. Voltage	110
Spacing	3 or 5 metres
Cable Specifications:	
Cable length	Bespoke to clients requirements
Cable diameter (mm)	0.75, 1.0, 1.5 or 2.5
Cable types	Standard Arctic Grade or LSOH
Conductor material	Copper
Temperature range	-40 to +70°C
Flexibility standard	318
Sheath colours available	Any
Number of cores	2, 3, 4, 5, 6 & 7
Standard	BE EN 50525-3-11:2011
Approved by	BS EN 50575:2014+A1:2016

Product Code

Moulded Light Adaptor BC	Product Code:	IV/FES/MLA/BC
Moulded Light Adaptor ES	Product Code:	IV/FES/MLA/ES
Lamp Guard	Product Code:	IV/FES/LG

IVIC LTD

4 Winchester Drive
South West Industrial Estate
Peterlee
Co. Durham
SR8 2RJ
www.ivicltd.com