



Figure-8 cable



Piercing
Sockets



Cable Adaptor



Bespoke Festoon Lighting System Utilising Figure-8 Cable, Piercing Sockets & Cable Adaptor

The Piercing Sockets unique design allows it to be fitted to the Figure-8 cable to suit the clients requirements. The complete system is designed to be used with any luminaire.

Features and Benefits

- **2-Core Figure-8 cables, available in Standard or Low Smoke Zero Halogen**
- **Piercing Sockets can be flexibly spaced at the clients requirements**
- **Compatible with any luminaire**
- **Robust and waterproof design**
- **Quick, safe and easy installation**
- **Cable length bespoke to clients specifications**

Applications

- **Ship Building & Ship Repair**
- **Construction**
- **Tunnelling**
- **Railways**

Specification

Cable Specifications:	
Cable length	Bespoke to clients requirements
Cable diameter	2 x 2.5 millimetres
Cable types	Standard or LSOH
Sheath colours available	Any
Conductor Material	Copper
Standard	BE EN 60332-1-2:A1:2016
Approved by	BE EN 505752014+A1:2016
Adaptor Specifications:	
Max. Voltage	400
Adaptor spacing	Flexible
Conductor size	0.5 to 1.5 sq mm
Adaptor temperature range	-20 to +125°C
IP rating	65

Product Code

TeePlug Piercing Light Socket	Product Code:	IV/THB/370/A2A
TeePlug 2 Cable Adaptor	Product Code:	IV/THB/384/P2A

IVIC LTD

4 Winchester Drive
South West Industrial Estate
Peterlee
Co. Durham
SR8 2RJ
www.ivicltd.com